

Exam : 000-972

Title : ILE RPG Programmer

Version : Demo

1. Which of the following operation codes is supported in both fixed form and /Free form?

A.CALL

B.EVALR

C.ALLOC

D.EXTRCT

Answer:B

2.Which of the following SQL statements, when used by itself in an RPG program, can take the place of a File Specification, a key and a CHAIN?

A.FETCH B.SELECT INTO C.DECLARE CURSOR D.PREPARE STATEMENT

Answer:B

3.Given the following code sample, what value is displayed? D MyDS DS D FieldA 5A Inz('XXXX') /free FieldA = 'VWXYZ'; Reset FieldA; Dsply ('FieldA=' + FieldA); *INLR = *On; BegSR *InzSR; FieldA = 'ABCDE'; EndSR;

A.FieldA=

B.FieldA=VWXYZ

C.FieldA=ABCDE

D.FieldA=XXXXX

Answer:C

4.Which of the following is an advantage gained by using a prototype and CALLP for a program call in place of CALL and PARM operations?

A.Ability to qualify the name of the program being called

B.Ability to have the compiler validate the parameters being passed

C.Ability to use a variable to contain the name of the program to be called

D.Ability to statically bind a program object to its caller for better performance

Answer:B

5.What is the purpose for the following reserved words? XML_START_ELEMENT XML_COMMENT XML_CHARS XML_END_ELEMENT

A.Aids in parsing XML using the DOM (Document Object Model).

B.Indicates the type of data entity to create during XML generation.

C.Aids in interpreting the event parameter in an event handling procedure.

D.Indicates to the parser which events your handler should be notified of.

Answer:C

A.MyPrice = CustPrice(1 : MyItem : *omit);

B.MyPrice = CustPrice(1 : MyItem : : MyQty);

C.MyPrice = CustPrice(MyCompany : MyItem : *omit : *nopass);

D.MyPrice = CustPrice(MyCompany : MyItem : MyContract : *omit);

Answer:A

7.Given the following code sample: d NotLate PR ExtPgm('LARRY') d RqDta 32767a d RqLen 10i 0 d RqTyp 10i 0 Which of the following is the correct code to call the program Larry?

A.call NotLate(RequestData : RequestLength : RequestType);

B.callb NotLate(RequestData : RequestLength : RequestType);

C.callp NotLate(RequestData : RequestLength : RequestType);

D.C CALL 'NOTLATE' C PARM RequestData C PARM RequestLength C PARM RequestType

Answer:C

8.File CUSMS contains a field named CMCSNO. Which of the following file specification keywords will allow the program to recognize this field as CUSTCSNO?

A.PREFIX(CUST)

B.PREFIX(CUST:2)

C.RENAME(CM:CUST)

D.RENAME(CMCSNO:CUSTCSNO)

Answer:B

9.A service program comprised of 6 modules has a custom signature. A new procedure with the EXPORT keyword has been added to one of the module sources. This procedure is not yet referenced by any programs. Which of the following is the correct sequence of tasks required?

A.Recompile *MODULE, modify binder source, update *SRVPGM

B.Recompile *MODULE, modify binder source, update *SRVPGM, recreate dependent programs

C.Modify binder source, update *SRVPGM, recompile *MODULE, recreate *PGM objects bound to the *SRVPGM

D.Recompile *MODULE, update *SRVPGM, modify binder source, recreate *PGM objects bound to the *SRVPGM

Answer:A

D.A qualified field name

Answer:B