

IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

Exam : HP0-236

**Title : Supporting SAN
Infrastructure & Solutions**

Version : DEMO

1.What should be the maximum number of active storage controller ports per inter-switch link in a high throughput computing environment?

- A.2
- B.4
- C.10
- D.20

Correct:D

2.Which factor can reduce the performance between devices in a Fibre Channel SAN?

- A.hop count
- B.switch latency
- C.inter-switch link latency
- D.inter-switch link congestion

Correct:D

3.Which ports should you use on a B-series switch to establish two Wavelength Division Multiplexing links to a remote site?

- A.ports which belong to the same "Quad"
- B.ports which belong to different "Quads"
- C.ports on different switches
- D.only 2 Gbps ports

Correct:B

4.What do you recommend if a performance bottleneck is discovered on a link between a 1 Gbps and a 2 Gbps B-series switch?

- A.Implement trunking on this link.
- B.Implement port channeling on this link.
- C.Use multi-mode cable instead of single mode.
- D.Replace the 1 Gbps switch with a 2 Gbps switch.

Correct:D

5.A complex SAN designed for applications with small IOs is used primarily by applications with large IOs. What is the impact to the SAN?

- A.The supported hop count is reduced.
- B.There may be congestion on inter-switch links.
- C.None. SAN design is not dependent on application IO size.
- D.The buffer-to-buffer credit on the storage system must be recalculated.

Correct:B