

IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

Exam : **HP0-763**

Title : NonStop Kernel Systems
Management and
Operations

Version : DEMO

1.What is an indicator of a poorly performing system?

- A.page-faults of 0.01 per second
- B.processor imbalance of 5 %
- C.queue-length of 10
- D.transaction rate of 10 transactions per second

Correct:C

2.What is the objective of capacity planning?

- A.To justify the return on investment and determine user community satisfaction.
- B.To ensure the system is fully utilized and there is no resource contention.
- C.To ensure that the system is well balanced and meeting the service level agreement.
- D.To determine if or when additional capacity is needed to meet the SLA.

Correct:D

3.Which NonStop Himalaya S-series NonStop Kernel tool is used to perform capacity planning?

- A.TPM
- B.TPDC
- C.TCM
- D.GPA

Correct:C

4.What are the benefits of running a program in native mode? Select TWO

- A.allows TNS and native code to be combined
- B.allows to run as high-PIN
- C.object file size is significantly larger
- D.larger stack space is supported
- E.runs faster than TNS and accelerated code

Correct:D E

5.Which utility is used to determine the current number of index levels in a key-sequenced file?

- A.NSX
- B.PEEK
- C.FUP
- D.TCM

Correct:C

6.Which SCF command will save the current disk configuration to a file named CONF0102?

- A.SAVE CONFIGURATION CONF0102
- B.SAVE CONFIGURATION 1.2
- C.SAVE DISK, FILE CONF0102
- D.OBEY FORM /OUT CONF0102/ DISK

Correct:B

7.Which tool is used to revert to a previously saved system configuration database?

- A.DSM/SCM
- B.SQLCI
- C.TSM
- D.SCF

Correct:C

8.Which facility is used to forward events from the primary collector (\$0) to the TSM console?

- A.EMS alternate collector
- B.compatibility distributor
- C.EMS trap subagent
- D.TSM service application

Correct:B

9.Which DSM facility provides event collection, logging, and distribution facilities?

- A.TM/MP
- B.EMS
- C.SQL
- D.DSM/SCM

Correct:B

10.Burst detection and suppression is used to

- A.limit network bandwidth use
- B.delete rapid and repetitive events
- C.minimize voltage fluctuations
- D.control the growth of SQL tables

Correct:B

11.Processor lock-step processing, mirrored disks, and TM/MP support which key feature of the NonStop Himalaya server?

- A.data integrity
- B.linear expandability
- C.manageability
- D.security

Correct:A

12.How do EMS filter tables simplify the writing of filters?

- A.They can be used with both collectors and distributors.
- B.They are text files that do not require compilation.
- C.They cannot be modified dynamically.
- D.They allow specification of individual token values.

Correct:B

13.What is the maximum number of lines a SWAN concentrator can support?

- A.6
- B.8
- C.16
- D.32

Correct:A

14.Which facility automatically delivers customized support information?

- A.IPM scout
- B.Express Notice
- C.Compaq TWS
- D.Integrity scout

Correct:B

15.What is NOT a reason for audit-trail files to be pinned on an audit-trail volume?

- A.might be needed to restart TMF

- B.might be needed to recover datavolume
- C.might be needed to stop and start RDF updaters
- D.current file

Correct:C

16.You encounter the message "STATUS - * 1077 * PATHMON, TAKEOVER BY BACKUP" on a PATHWAY subsystem. What is the recommended action?

- A.Switch the PATHMON back to the configured primary processor and see if the failure occurs again.
- B.Check if there has been a process or processor failure or an operator has issued a command to switch the primary process.
- C.Ignore the message because the backup process is still running and no application outage has occurred.
- D.Perform a processor dump and provide a copy of the EMS log and PATHWAY PATHCTL file to your support service provider.

Correct:B

17.Which command monitors system and application Event Management Service (EMS) messages?

- A.STATUS prog *, cpu *, out \$home, detail on
- B.EMSDIST type p, collector \$0, textout \$home
- C.EMSVIEW in \$0, out \$term, time all ,detail on
- D.SYSLOG emslog *, outdev \$term, type f, status *

Correct:B

18.Which TSM application sets the VADS (Value Added Diagnostics) password?

- A.low level link
- B.notification director
- C.SP tool
- D.service connection

Correct:B

19.Which command allows the implementation of a TM/MP software IPM into a running TM/MP configuration?

- A.ALTER TMF
- B.ALTER PROCESS
- C.ALTER DATAVOL
- D.ALTER AUDITTRAIL

Correct:B

20.Which tool is used to view TSM alarms?

- A.SP Tool
- B.low level link
- C.service application
- D.guided replacement toolkit

Correct:C