

# IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

**Exam : HP0-S39**

**Title : BladeSystem Networking**

**Version : Demo**

1.What are the differences between a Virtual Connect Flex-10/10D module and a Virtual Connect FlexFabric module? (Select two.)

- A. The Flex-10/10D module uses the native Fibre Channel protocol on the uplink ports that connect to a SAN switch or directly to an HP 3PAR storage array.
- B. A Flex-10/10D module supports LAN and iSCSI access and supports uplink connectivity to a SAN or LAN using ports X1 through X4.
- C. A Flex-10/10D module does not support FCoE single-hop connections when a SAN switch is directly connected to the module.
- D. A Flex-10/10D module supports 4x 10GbE-KR internal cross-connect ports, which are all dedicated

**Answer:** C,D

2.An HP BladeSystem C7000 enclosure has Virtual Connect FlexFabric modules with FlexNIC adapters. A server profile has the following custom bandwidth settings:

- Network1: 4 Gb
- Network2: 8 Gb
- Network3: 10 Gb
- Network4: Auto

What is the effective minimum bandwidth of Network4?

- A. 10 GB
- B. 4 GB
- C. 8 GB
- D. 2 GB

**Answer:** D

3.An administrator plans to use a centralized user database for Virtual Connect.

Which user database does Virtual Connect support?

- A. MySQL Server
- B. Oracle
- C. Active Directory
- D. SQL Server

**Answer:** D

**Explanation:**

Reference: [http://h20565.www2.hp.com/hpsc/doc/public/display?docId=emr\\_na-c02537509](http://h20565.www2.hp.com/hpsc/doc/public/display?docId=emr_na-c02537509)

4.A customer has four HP BladeSystem c7000 enclosures with Virtual Connect FlexFabric modules as part of a single Virtual Connect domain. The customer wants a single location to manage all Virtual Connect modules.

What must the customer use?

- A. HP Virtual Connect Manager
- B. HP Onboard Administrator
- C. HP Virtual Connect Enterprise Manager
- D. HP Intelligent Management Center

**Answer:** C

**Explanation:**

Reference: <http://www8.hp.com/us/en/products/server-software/product-detail.html?oid=3601866>

5.Which network aspects can be used by the Virtual Connect to load balance traffic in a link aggregation group? (Select two)

- A. IP address and protocol port
- B. Physical port
- C. Cable type
- D. MAC address

**Answer: D**

**Explanation:**

Reference: [http://h20565.www2.hp.com/hpsc/doc/public/display?docId=emr\\_na-c01386629](http://h20565.www2.hp.com/hpsc/doc/public/display?docId=emr_na-c01386629)