

Exam : JN0-250

Title : Mist AI. Associate (JNCIA-MistAI)

Version : DEMO

1. You configured an 802.11n AP to use the 2.4 GHz frequency band and 20 MHz channel width.

In this scenario, how many non-overlapping channels are available for clients to use in Europe? A. 11

- B. 4
- C. 1
- D. 6

Answer: B

2. Which SLE would you use to determine Wi-Fi interference?

- A. AP Uptime
- B. Roaming
- C. Successful Connects
- D. Capacity

Answer: D

Explanation:

Reference: https://www.mist.com/documentation/service-level-expectations-sle/

3. Which device is responsible for roaming decisions?

- A. user
- B. client
- C. controller
- D. AP

Answer: B

Explanation:

Reference: http://wifinigel.blogspot.com/2015/03/what-are-sticky-clients.html

4. When using the Mist Cloud with Mist APs, which statement is correct?

- A. User data is terminated in the cloud and run through a firewall.
- B. User data is compressed and terminated in the cloud.
- C. User data is terminated in the cloud and forwarded.
- D. User data is bridged locally.

Answer: D

Explanation:

Reference:

https://www.techtarget.com/searchnetworking/news/252473829/Juniper-taps-Mist-Systems-for-wired-wir eless-LAN-analytics

5. Which two statements are correct about Marvis? (Choose two.)

- A. Marvis is the main configuration tool.
- B. Marvis lets you ask questions about your network.
- C. Marvis will send custom reports.
- D. Marvis can be used as a proactive monitoring tool.

Answer: B,D

Explanation:

Reference: https://www.mist.com/resources/mist-marvis-overview/