

# IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

**Exam** : **642-737**

**Title** : Implementing Advanced  
Cisco Unified Wireless

**Version** : DEMO

1.Which two considerations must a network engineer have when planning for voice over wireless roaming?  
(Choose two.)

- A. Roaming with only 802.1x authentication requires full reauthentication.
- B. Full reauthentication introduces gaps in a voice conversation.
- C. Roaming occurs when e phone has seen at least four APs.
- D. Roaming occurs when the phone has reached -80 dBs or below.

**Answer:** A,B

2.Which three of the items listed are required configuration parameters for the WLC to enable NAC out-of-band single sign-on when implementing NAC appliances? (Choose three.)

- A. EAP authentication
- B. web authentication
- C. SNMP
- D. RADIUS accounting
- E. WLAN > SNMP NAC enabled
- F. WLAN > RADIUS NAC enabled

**Answer:** C,D,E

3.An engineer is responding to a man-in-the-middle attack and needs to enable security features to prevent such attacks in the future. What security feature would prevent a manin-the-middle attack?

- A. Management Frame Protection
- B. ACL
- C. Enable client and infrastructure MFP
- D. AAA Override

**Answer:** C

4.Refer to the exhibit.

The screenshot shows the 'WLANs > Edit' configuration page in Cisco WLC v7.0, with the 'Security' tab selected. The configuration is as follows:

- General:**
  - Allow AAA Override:  Enabled
  - Coverage Hole Detection:  Enabled
  - Enable Session Timeout:  1800 (Session Timeout (secs))
  - Aironet IE:  Enabled
  - Diagnostic Channel:  Enabled
  - IPv6 Enable:
  - Override Interface ACL: None
  - P2P Blocking Action: Disabled
  - Client Exclusion:  Enabled, Timeout Value (secs): 0
- HREAP:**
  - H-REAP Local Switching:  Enabled
  - Learn Client IP Address:  Enabled
- DHCP:**
  - DHCP Server:  Override
  - DHCP Addr. Assignment:  Required
- Management Frame Protection (MFP):**
  - Infrastructure MFP Protection:  (Global MFP Disabled)
  - MFP Client Protection:  Optional
- DTIM Period (in beacon intervals):**
  - 802.11a/n (1 - 255): 1
  - 802.11b/g/n (1 - 255): 1
- NAC:**
  - State:  Enabled

What is the effect of setting Client Exclusion to Enabled and set to a Timeout Value of 0 seconds in a Cisco WLC v7.0?

- A. Excluded clients must be manually removed from the excluded list.
- B. Client exclusion will not occur.
- C. Client exclusion timeout will be determined by the IDS module.
- D. Clients will only be disconnected and not excluded.

**Answer: A**

5.What NAC appliance component is configured to create user roles, meet remediation requirements, and handle checking for device compliance?

- A. NGS
- B. NAA
- C. NAS
- D. NAM

**Answer: D**