

# IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

**Exam** : **9A0-327**

**Title** : Adobe CQ 5.5 Component  
Developer ACE Exam

**Version** : DEMO

1.Which is the correct way to get the ValueMap of a resource?

- A.resourceResolver.adaptTo(ValueMap.class)
- B.resource.adaptTo(ValueMap.class)
- C.currentNode.getValueMap()
- D.currentPage.getValueMap()

**Answer: B**

2.Which option do you need to add to the Java-based crx-quickstart command to specify that you will be using an LDAP authentication?

- A.Dcom.day.crx.core.CRXUserManagerImpl=crx-quickstart/server/etc/ldap\_login.conf
- B.Djava.security.auth.login.config=crx-quickstart/server/etc/ldap\_login.conf
- C.Dcom.day.crx.security.ldap.LDAPLoginModule=required
- D.Dcom.day.crx.security.ldap.principals.LDAPPrincipalProvider=crx-quickstart/server/etc/ldap\_login.conf

**Answer: B**

3.How do you create a configuration for an OSGi bundle within CRX that is specific to only the author instance?

- A.Add a property called "run\_mode" to the node sling:OsgiConfig and assign it the value "author".
- B.Use the CRX browser to create a folder in /apps/myproject called "author" and then create a new node and select "nt:unstructured" as the node type.
- C.Use the CRX browser to create a folder in /apps/myproject called "author" and then create a new node and select "sling:OsgiConfig" as the node type.
- D.Use the CRX browser to create a folder in /apps/myproject called "config.author" and then create a new node and select "sling:OsgiConfig" as the node type

**Answer: D**

4.During a workflow step a comment is added requiring an update of a paragraph on a Web page.Where does the workflow author make the change?

- A.In the content page within the workflow step.
- B.In the Workflow Model.
- C.In the Workflow Instance.
- D.In the design page.

**Answer: A**

5.Which method of the ResourceResolver Interface uses resources mapping to retrieve property values?

- A.resolve().
- B.getResource().
- C.map().
- D.getSearchPath().

**Answer: A**

6.How does the OSGi installer manage a bundle if a bundle with the same symbolic name is already installed?

- A.It uses the new bundle only if it has a higher version.

- B.Stops the current bundle and allows the user to select which one to start.
- C.Keep the old one and write an error to the log file.
- D.The previous bundle is replaced by the last provided bundle.

**Answer: A**

7.How do you create a design dialog for a CQ component?

- A.Create a dialog in the component folder and set the dialog's xtype property to designDialog.
- B.Create a dialog in the component folder and name it design\_dialog.
- C.Create the same component path structure under the design page and create the dialog there.
- D.Create a node under the component's dialog node and set the xtype property to designDialog.

**Answer: B**

8.You want to use a different page properties dialog instead of the one out of the box.How do you configure it?

- A.Create a dialog in the page-component folder referenced by the template definition via sling:resourceType and name it "dialog".
- B.Create a dialog in the template definition node and name it pageProperties.
- C.Create the dialog in the template definition node, name it "dialog" and add a property xtype with the value pageProperties.
- D.Create the dialog in the foundation's page-component node and name it the same as your template definition.

**Answer: A**

9.What is the purpose of a Closed User Group?

- A.To define a selected group of authors with special authoring permissions
- B.To define one or more Web pages on the publish instance accessible only by members of the Closed User Group
- C.To define a group of users and assign them admin rights to manage workflows
- D.To define a group of users that have special privileges to do system support

**Answer: B**

10.What is the purpose of sending values as selectors in the URL instead of sending them as query parameters?

- A.To avoid caching the response in the Web server.
- B.To enable the response to be cached in the Web server.
- C.To avoid creating a session object in the application server.
- D.To improve security.

**Answer: B**