

# IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

**Exam** : **HP0-A17**

**Title** : Install,Maintain and  
Upgrade Nonstop Himalaya  
Hardware

**Version** : DEMO

**1.Which tool can be used to force a reboot of a SWAN/SWAN 2 CLIP?**

- A.WANDUMP
- B.WANFBT
- C.WANLNCK
- D.WANTCB

**Correct:B**

**2.Which components can you install on the system console using the OSM Installer DVD ? (Select two.)**

- A.Event Viewer
- B.Low Level Link
- C.Notification Director
- D.Service Connection

**Correct:B C**

**3.When replacing a PMF, within how much time must the power cable be reconnected?**

- A.15 seconds
- B.20 seconds
- C.25 seconds
- D.30 seconds

**Correct:C**

**4.What is used to replace a SWAN/SWAN2 concentrator?**

- A.WAN Wizard PRO
- B.Guided Procedures
- C.SCF
- D.SP Tool

**Correct:C**

**5.The SP Tool has identified a faulty X fabric cable between enclosure 1 and enclosure 3. Which connector on the SEB in enclosure 1 is affected?**

- A.1
- B.2
- C.3
- D.4

**Correct:B**

**6.Using the HP suggested naming convention, identify the G4SA group, module, slot and port number of LIF L112E.**

- A.GRP-11, MOD-2, SLOT-2, PORT-E
- B.GRP-112, MOD-2, SLOT-2, PORT-E
- C.GRP-11, MOD-2,SLOT-2, PORT-A
- D.GRP-112, MOD-2, SLOT-2, PORT-A

**Correct:C**

**7.Which action is required before replacing an X Fabric fiber-optic cable between MSEB and Switch-to-Node ports?**

- A.Verify that internal Y fabric for all other nodes are fully operational.
- B.Verify that external Y fabric for all other nodes are fully operational.
- C.Verify that both internal and external Y fabric for all other nodes are fully operational.

D. Verify that both external X and Y fabric for all other nodes are fully operational.

**Correct: C**

**8. Which preventive maintenance tasks are performed on an S-series server? (Select two.)**

- A. testing the fiber optic cables
- B. cleaning tape drives regularly
- C. running diagnostics on all devices
- D. dusting or cleaning enclosures as needed
- E. running traces on all communication lines

**Correct: B D**

**9. To display all of the Fiber Channel Disks installed on the system along with their path states, what step(s) must be taken from the OSM Service Connection?**

- A. Click the Logical Status icon, logon using the pop-up window, and then click on the FC Disk resource type.
- B. Click the Display icon and then choose the Attributes menu selection.
- C. Click the Summary icon and then choose the Connection Status menu selection.
- D. Click the Tools icon and then choose the Physical Configuration Tool menu selection.

**Correct: A**

**10. To view the entire hardware inventory of the system, what steps must be taken?**

- A. Select the system item in the hierarchical view, and then use the display Menu attributes item.
- B. Right-click on the system item in the hierarchical view, and then select the attributes sub-menu item.
- C. Double-click on the system item in the hierarchical view.
- D. Select the system item in the hierarchical view, and then change the view from physical to inventory.

**Correct: D**

**11. Which parameters may be used to initiate a search in the TSM/OSM Event Viewer?**

- A. time frame, node number, system number
- B. time frame, cluster number, SYSnn
- C. time frame, system name, timezone offset
- D. time frame, source, subsystem

**Correct: D**

**12. Which utility displays the network route between the user's host and a remote host?**

- A. PING
- B. trace
- C. tracer
- D. ptrace

**Correct: C**

**13. What can be used to test a tape drive while troubleshooting a NonStop S-series system? (Select two.)**

- A. SP Tool
- B. TFDS
- C. backup/restore
- D. tapecom
- E. OSM Service Connection

**Correct: C E**

**14. Where can Automatic Data Collection be enabled?**

- A.TACL
- B.SCF
- C.OSM Service Connection
- D.OSM Low Level Link

**Correct:C**

**15.Which OSM file is needed for analysis of a Hardware Error Freeze (HEF) on an S-series system?**

- A.ZZPSnnnn
- B.ZZAAnnnn
- C.ZZSAAnnnn
- D.CONFxyxy

**Correct:A**

**16.Which object in OSM Service Connection displays enclosure voltages?**

- A.PMF
- B.PMCU
- C.processor
- D.power supply

**Correct:A**

**17.If you suspect a problem with a disk adapter, which subsystems in OSM Event Viewer should you select to view applicable events? (Select two.)**

- A.SMD
- B.SLSA
- C.STORAGE
- D.IPC
- E.CPU

**Correct:A C**

**18.An eight-processor system has all processors down with software halts. A tape drive is connected to the PMF 1.1.50. Which processors can be dumped to tape?**

- A.Even numbered processors only.
- B.Odd numbered processors only.
- C.Processors 0 and 1 only.
- D.All eight processors in the node.

**Correct:D**

**19.On a system where all processors are halted, which adapter locations can be specified to perform a tape dump? (Select two.)**

- A.PMF 1,1,50
- B.PMF 2,1,50
- C.PMF 1,1,55
- D.PMF 11,1,50
- E.SNDA 1,1,51

**Correct:A C**

**20.What are the three types of HotStuff messages?**

- A.general, OPN, SPR recall and withdrawal
- B.general, release highlights, SPR recall and withdrawal
- C.release highlights, OPN, SPR recall and withdrawal

D.general, OPN, release highlights

**Correct:A**