IT认证电子书

质　量　更　高　　服　务　更　好

半年免费升级服务

http://www.itrenzheng.com

Exam : **HPE6-A42**

Title : Implementing Aruba WLAN (IAW) 8

Version : DEMO

1.Refer to the exhibit.

```
(MM) ^[mynode] #show airmatch solution

Seq  Time              Aps  [5GHz] Radios Cost Conflict Deploy  [2GHz] Radios Cost Confli
#2  20161230_05:04:51   1            1    1.0      0.0 No                1   4.0      0
#1  20161228_12:45:24   1            1    1.0      0.0 Yes               1   4.0      0

(MM) [mynode] #show airmatch solution 2

# 20161230_05:04:51 Scheduled
# 5GHz   capacity/network cost/solution cost/improvement: 4.0/1.0/1.0/0.0%
# 2.4GHz capacity/network cost/solution cost/improvement: 1.0/4.0/4.0/0.0%
# Band Radio            Mode Chan  CBW    EIRP (dBm)   APName
  5GHz 70:3a:0e:59:81:30  AP    157i   80.          18.  EastAP
  2GHz 70:3a:0e:59:81:20  AP      1i   20*           9.  EastAP

[*] regarded frozen | [.] no change | [i] channel ignored because insufficient quality i
```

An Aruba solution uses AirMatch with the default AirMatch profile settings. A network administrator sees that a scheduled optimization was completed, but a plan was not deployed.

Based on the exhibit, why did this occur?

A. The cost of the new plan exceeds the amount allowed by the feature license

B. The new plan did not offer significantly improved quality

C. The solution uses master-local mode

D. ARM is disabled in the radio profile, so AP radios are considered frozen

Answer: B

2.Refer to the exhibit.



Network administrators need to set up a WLAN that uses WPA2 encryption and authenticates users with a preshared key (PSK) that is the same for all users. Administrators do not see where they should specify the option for the preshared key.
What should the administrators do?
A. Click Personal in the slide bar.
B. Click the + icon in the Authentication server section
C. Return to the first page in the wizard and select the guest option
D. Configure an L3 authentication profile after the WLAN wizard is complete
Answer: A

3.What is a reason for a company to choose to deploy an Aruba 7024 Mobility Controller (MC) rather than an Aruba 7010 MC?
A. to support 802.11ac Aps rather than only 802.11n APs
B. to support more wireless users
C. to support more POE devices directly connected to the MC
D. to support a faster firewall throughput rate
Answer: C

4.A company wants to provide wireless access for guests with their Aruba solution.

Which configuration feature requires the customer to purchase PEFNG licenses?
A. redirection of guests to an external captive portal
B. provision of DHCP services to unauthenticated guests
C. addition of custom rules to control access for authenticated guests
D. customization of the internal captive portal login page
Answer: C

5.A company has an Aruba Mobility Master (MM)-based solution. A network administrator wants to collect and analyze information about clients and access points (APs) over extended periods of time.
What should the administrator do to achieve this goal?
A. Add Aruba AirWave to the solution.
B. Run a Traffic Analysis report on the MM.
C. Make sure that MM has sufficient AppRF licenses.
D. Enable archival from the MM interface Maintenance windows.
Answer: A