

IT 认证电子书



质 量 更 高 服 务 更 好

半年免费升级服务

<http://www.itrenzheng.com>

Exam : **JN0-341**

Title : ER.Associate(JNCIA-ER)

Version : DEMO

1.Which command copies the factory-default files to your backup media?

- A.request system snapshot rescue
- B.request system snapshot factory
- C.request system snapshot default
- D.request system snapshot as-primary

Correct:B

2.What are two methods of accessing a Juniper enterprise router? (Choose two)

- A.RSH
- B.HTTPS
- C.console
- D.J-Config

Correct:B C

3.What is the default route preference for static routes?

- A.0
- B.5
- C.10
- D.170

Correct:B

4.What is shown by the command show interfaces extensive fe-0/0/0 but not shown by the command show interface detail fe-0/0/0?

- A.input error counter
- B.interface MTU size
- C.input packets counter
- D.the IP address on logical interface fe-0/0/0.0

Correct:A

5.What does the number one (1) represent for interface fe-0/0/1?

- A.port number
- B.PCI slot number
- C.channel number
- D.virtual PIC number

Correct:A

6.What are two functions of the Intel IXP processors? (Choose two.)

- A.Keepalives
- B.route-lookup
- C.CRC validation
- D.Layer 2 decapsulation

Correct:A C

7.Which CLI command will ping destination 10.0.29.1 ten times and display the incoming interface of the received packet?

- A.ping count 10 10.0.29.1 detail
- B.ping number 10 10.0.29.1 detail
- C.ping count 10 10.0.29.1 extensive
- D.ping number 10 10.0.29.1 extensive

Correct:A

8.Which J-Web menu displays the users currently logged into the CLI?

- A.Monitor > Users
- B.Manage > Users
- C.Monitor > System
- D.Manage > System

Correct:C

9.Which multicast address does RIPv2 use for route updates by default?

- A.224.0.0.2
- B.224.0.0.5
- C.224.0.0.9
- D.255.255.255.255

Correct:C

10.Which two statements regarding system logging on a Juniper enterprise router are correct? (Choose two.)

- A.The system log has a proprietary format.
- B.System logs must be sent to a remote device.
- C.New system logs can be created and archived.
- D.Most software processes create their own logs.

Correct:C D

11.In configuration mode you see the following prompt: [edit interfaces fe-1/1/1] user@router# Which command will take you to operational mode?

- A.end
- B.exit
- C.quit
- D.exit configuration-mode

Correct:D

12.Which three options can be used with the load CLI command? (Choose three.)

- A.merge
- B.replace
- C.partial
- D.complete
- E.override

Correct:A B E

13.Click the Exhibit button. In the exhibit, the protect-re filter is applied as an input filter on the lo0.0 interface and all possible services are enabled under [edit system services]. Which two methods can you use to access the router? (Choose two.)

```
[edit]
instructor@R2# show firewall
family inet {
  filter protect-re {
    term 1 {
      from {
        protocol tcp;
        destination-port ssh;
      }
      then accept;
    }
    term 2 {
      from {
        protocol tcp;
        destination-port http;
      }
      then accept;
    }
  }
}
```

- A.FTP
- B.SSH
- C.Telnet
- D.J-Web

Correct: B D

14. Which type of IGP should you use to achieve scalability in a large enterprise network?

- A.link-state protocol
- B.path-vector protocol
- C.Bellman-Ford protocol
- D.distance-vector protocol

Correct: A

15. The J-Web application can install the JUNOS software from which two locations? (Choose two.)

- A.SDX
- B.local PC
- C.BSD shell
- D.remote host

Correct: B D

16. How many committed configuration files are stored on the Juniper Networks enterprise router?

- A.4
- B.15
- C.48
- D.50

Correct: D

17. Which CLI command displays all OSPF LSAs received by the local router?

- A.show ospf neighbor
- B.show ospf database
- C.show ospf interface
- D.show ospf adjacency

Correct:B

18.Which two field-replaceable units (FRUs) are hot-swappable? (Choose two.)

- A.Routing Engine on M10i
- B.Physical Interface Card on M7i
- C.fan tray on J-series routers
- D.Physical Interface Modules on J6300 router

Correct:A B

19.Which three initial configuration methods are supported on J-series routers? (Choose three.)

- A.CLI
- B.J-Web
- C.JUNOScope
- D.autoinstallation
- E.PCMCIA flash card

Correct:A B D

20.What is one configuration method for loading a factory default configuration onto a J-series router?

- A.load override reset
- B.load factory-default
- C.rollback factory-default
- D.request system factory-default

Correct:B